

PRODUCT DATA SHEET

TRANSAX 80W90 & 85W140 GL5

DESCRIPTION

Transax 80W90 and 85W140 gear oils are blended to the GL5 classification and are used in the gearboxes and differentials of the majority of road vehicles. Transax 80W90 meets the requirements of nearly all passenger vehicles and light trucks. They have excellent extreme pressure properties and provide excellent protection against wear, corrosion and oxidation.

Grade	80W90	85W140
Viscosity (Typical cSt @ 40°C)	156	360
Viscosity (Typical cSt @ 100°C)	15.5	27.2

APPLICATION

Transax 80W90 gear oil is designed for manual gearboxes and transfer cases and differentials where an 80W, 80W90 or SAE 90 gear oil is specified, whilst Transax 85W140 generally is used in heavier vehicles where 85W140 or SAE 140 gear oils are specified. They are designed for passenger vehicles, light trucks, heavy trucks and off-road equipment.

STANDARDS

Meets or exceeds the following:

SAE Grade: 80W90, 85W140

API: GL5, MT-1

MACK: GO-J

MIL-PRF-2105E

SAE J2360

CONTAINER SIZES

Bulk, 1000 Litre IBC, 205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre

Issue Date 27/10/22

Proven Protection. Powerful Performance.