



## **PRODUCT INFORMATION SHEET**

**Product Name: TRANSAX 80W90 and 85W140 GL5**

### **PRODUCT**

Prolube Transax 80W90 and 85W140 gear oils are blended to the GL5 classification and are used in the gearboxes and differentials of the majority of road vehicles. Transax 80W90 meets the requirements of nearly all passenger vehicles and light trucks. They have excellent extreme pressure properties and provide excellent protection against wear, corrosion and oxidation.

Grade	<b>80W90</b>	<b>85W140</b>
Viscosity (Typical cSt @ 40°C)	156	360
Viscosity (Typical cSt @ 100°C)	15.5	27.2

### **APPLICATION**

TRANSAX 80W90 gear oil is designed for manual gearboxes and transfer cases and differentials where an 80W, 80W90 or SAE 90 gear oil is specified, whilst Transax 85W140 generally is used in heavier vehicles where 85W140 or SAE 140 gear oils are specified. They are designed for passenger vehicles, light trucks, heavy trucks and off-road equipment.

### **STANDARDS**

Meets or exceeds the following:  
SAE Grade: 80W, 80W90, SAE 90 - SAE 140, 85W140.  
API: GL5 , MT-1  
MACK: GO-J  
MIL-PRF-2105E  
SAE J2360

### **CONTAINER SIZES**

205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre.

### **CONTACT**

#### ***PROLUBE Lubricants,***

P.O. Box 5435,  
15 Pinnacle Street,  
Brendale, Qld. 4500.

Telephone: (07) 3881 1733  
Fax: (07) 3881 1708  
Email: [admin@prolube.com.au](mailto:admin@prolube.com.au)  
Internet: [www.prolube.com.au](http://www.prolube.com.au)

Issue Date 27/9/2012