

PRODUCT DATA SHEET

TRANSDRIVE GL5 SERIES

(SEMI-SYNTHETIC GEAR OIL)

DESCRIPTION

Transdrive gear oil is a semi-synthetic blend meeting the GL5 classification and may be used in the gearboxes and differentials of the majority of road vehicles. Transdrive is a heavy duty product formulated to provide superior anti-wear, anti-scuffing and corrosion protection, maintained over a wide range of temperatures. Transdrive has excellent extreme pressure properties and provides excellent protection against oxidation.

Grade	90	140
Viscosity (Typical cSt @ 40°C)	168	324
Viscosity (Typical cSt @ 100°C)	16.8	26.8

APPLICATION

Transdrive gear oil is an excellent lubricant for differentials operating in heavily stressed conditions. It is recommended for use in all heavy duty applications and has been especially formulated for use in Rockwell Meritor Differentials.

STANDARDS

Meets or exceeds the following:

SAE Grade: 90 or 140

API: GL5

MACK: GO-J, MT-1

MIL-PRFP2105E

MAN 342 Type M2

SAE J2360

KOMATSU KES 07.861

ARVIN MERITOR 0-76-A 0-76-B 0-76-D

DAF

IVECO

Scania STO 1:0

ZF TE-ML 05A

ZF TE-ML 07A

ZF TE-ML 08

ZF TE-ML 12E

ZF TE-ML 16B

ZF TE-ML 16C

ZF TE-ML 16D

ZF TE-ML 17B

ZF TE-ML 19B

ZF TE-ML 21A

CONTAINER SIZES

Bulk, 1000 Litre IBC, 205 Litres, 20 Litres

Issue Date 1/9/19

Proven Protection. Powerful Performance.