

## PRODUCT DATA SHEET

# **AUTOMAX IIID**

## **(AUTOMATIC TRANSMISSION FLUID)**

### DESCRIPTION

Automax IIID is an Automatic Transmission Fluid formulated from high quality base oils blended with an excellent additive pack to provide a lubricant which meets the specific requirements of the GM Dexron® III specifications. Although Dexron® III is a General Motors specification for their vehicles, there are some hydraulic pump manufacturers who recommend the use of this fluid in their hydraulic pump applications.

Viscosity - Typical 6.0 cSt @ 100°C

### APPLICATION

Designed for automatic transmissions, power steering systems, fluid drive systems and hydraulic systems where a Dexron® III fluid is specified.

### STANDARDS

Meets or exceeds the following:

General Motors Dexron® III-H, III-G, III-F, III-E, III-D

Mercedes Benz 236.1, 236.5, 236.6, 236.7

ZF TE-ML 02F, 04D, 09, 11A, 14A, 17C

Voith 55,6335 and 55,6336

Allison C4, TES 389

Caterpillar TO-2

Chrysler Transmissions (except where MS-9602 or MS-7 176 is specified)

Ford Mercon®, Ford M2C138-CJ, M2C 166-H Fluids

Volvo 97340, 97341

MAN 339 Z1, V1, Z2, V2

Sperry, Vickers, Denison and Sunstrand for hydraulic pump systems.

### CONTAINER SIZES

205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litres

Issue Date 1/9/2019

*Proven Protection. Powerful Performance.*