



PRODUCT INFORMATION SHEET

**Product Name: SYNTEGRA GEAR OIL SERIES
Synthetic Industrial Gear Oils**

PRODUCT

Prolube Syntegra Gear Oil 150, 220, 320, 460 are fully synthetic industrial gear oils that are blended from the highest quality synthetic base oils together with the finest gear oil additives. They have outstanding thermal stability and provide excellent protection against corrosion. They are suitable for a wide range of applications in industry and mining.

Grade (ISO Viscosity)	150	220	320	460
Viscosity (Typical cSt @ 40°C)	150	220	320	460
Viscosity (Typical cSt @ 100°C)	18.0	23.5	30.0	36.5

APPLICATION

These oils are designed for a wide range of applications in industrial gear systems. Ideal for high temperature and longer drain applications.

STANDARDS

Meets or exceeds the following:

US Steel 224

AGMA: 250.04

Cincinnati Milacron

CONTAINER SIZES

205 Litres,

20 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinnacle Street,
Brendale, Qld. 4500.

Telephone: (07) 3881 1733
Fax: (07) 3881 1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au

Issue Date 11/10/2012