

PRODUCT DATA SHEET

SYNTEGRA GEAR OIL SERIES

(FULL SYNTHETIC INDUSTRIAL GEAR OIL)

DESCRIPTION

Syntegra Gear Oils are fully synthetic industrial gear oils that are blended from the highest quality synthetic base oils together with the finest gear oil additives. They have outstanding thermal stability and provide excellent protection against corrosion. They are suitable for a wide range of applications in industry and mining.

Grade	68	100	150	220	320	460	680
Viscosity (Typical cSt @ 40°C)	68	100	150	220	320	460	680
Viscosity (Typical cSt @ 100°C)	10.5	14.0	19.1	25.6	34.3	45.6	64.0
Viscosity Index	150	155	163	166	169	172	174
Density @ 15°C g/l	0.85	0.86	0.86	0.86	0.86	0.87	0.87
Pour Point °C	-42	-42	-42	-42	-42	-42	-42

APPLICATION

These oils are designed for a wide range of applications in industrial gear systems. Ideal for high temperature and longer drain applications.

STANDARDS

Meets or Exceeds the following:

US Steel: 224

AGMA: 250.04, 9005-EO2

Cincinnati Milacron

David Brown Type M, A and E

ISO 12925-1 CKC/CKD

DIN 51517 Part 3

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres
(Not all grades available in all sizes)

Issue Date 18/5/23