

## PRODUCT DATA SHEET

# PROSTOP DOT3

## (DISC BRAKE AND CLUTCH FLUID)

### DESCRIPTION

Prostop DOT 3 Disc Brake and Clutch Fluid is an inhibited blend of glycol ethers, corrosion inhibitors and fluid modifiers meeting the requirements of a general purpose hydraulic brake fluid.

It is specifically designed for the low to medium performance modern and early model car braking systems.

We recommend the fluid should be replaced every twelve months under average driving conditions.

### APPLICATION

Formulated for automotive drum brake, disc brake and hydraulically actuated clutch systems of early and late model vehicles where the manufacturer recommends using DOT 3 Fluid. Some Toyota models and other Japanese vehicles stipulate DOT 3 brake fluids.

### STANDARDS

Meets or exceeds the following:

AS/NZS 1960-1995 GRADE 1  
SAE J1703  
FMVSS No. 116 DOT3  
ISO 4925 Class 3

### PROPERTIES

Appearance: Amber Liquid  
ER Boiling Point °C: 240 - 260  
Wet ER Boiling Point °C: 150 Min  
Viscosity at -40°C: 1500 cSt Max

### CONTAINER SIZES

20 Litres, 5 Litres, 500 ml

Issue Date 1/10/2019