

PRODUCT DATA SHEET

HVX TURBO

(15W50 CI-4 SL)

DESCRIPTION

HVX Turbo 15W50 combines the very latest additive technology and high quality base oils to provide a lubricant with exceptional performance in the latest model turbo charged diesel and petrol engines. This product ensures less oil thickening; better oxidation and corrosion resistance, less wear and improved all-round performance. It is recommended for mixed fleet service where late model vehicles are in use, particularly where they work under hot or adverse conditions.

Viscosity - Typical 18.55 cSt @ 100°C

APPLICATION

Designed for 4 stroke motors using LP, ULP, PULP, LPG and diesel fuels particularly in high performance applications. It is specifically designed as an alternative to synthetic lubricants and as a means of maintaining component protection in high stress applications.

STANDARDS

Meets or exceeds the following or recommended for:

SAE Grade: 15W50

API CI-4, CH-4, SL, SJ

CUMMINS CES 20076, 77, 78

Mack EO-M PLUS

ACEA: E7 - 16 E7/B4/A3 - 07 E7/B4/B3/A3 - 04 E5/E3/B4/B3/A3 - 02

Mercedes MB 228.2 228.3

Volvo VDS 3

Renault RLD2

MTU Type 2

MAN 3275

CAT ECF 1a, ECF-2

Deutz DQC III-10

Detroit Diesel DDC 93K215

Global DHD-1

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres, 1 Litres

Issue Date 1/9/2019