



PRODUCT INFORMATION SHEET

XHP 4ST 10W40 SL CF Semi-synthetic, 4 Stroke Engine Oil

PRODUCT

Prolube XHP 4ST 10W40 SL CF is a latest generation semi-synthetic engine oil specifically developed for high performance four stroke motor cycle engines. It has a balanced additive system containing correct friction characteristics and antiwear additives to give excellent performance in high stress applications. The friction characteristics of the oil are designed to give the correct level of wet clutch operation when combined with the gearbox.

Viscosity

Typical 13.1 cSt @ 100°C

APPLICATION

This oil is designed for most modern four stroke motor cycles with combined engine, transmission and wet clutches systems. It is also suitable for motorcycles where the engine is separate from the transmission. Prolube XHP 4ST oil gives superior protection for components encountering lower temperature operation with cold starts.

STANDARDS

Meets or exceeds the following:

SAE Grade: 10W40

API: SL CF

JASO: MA

CONTAINER SIZES

205 Litres,

20 Litres,

5 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au

Issue Date 17/7/14