

## PRODUCT DATA SHEET

# PROSUPERPLANT GREASE

## DESCRIPTION

Prosuperplant Grease is an extremely high quality product with excellent lubrication characteristics for the range of anti-friction and plain bearings, gears and couplings in automotive, marine, agricultural and industrial applications requiring a grease with a high base oil viscosity and weld load. It is based on a lithium complex thickener, high quality paraffinic and polybutene base stocks combined with the inclusion of extreme pressure additives, effective rust, oxidation and corrosion inhibitors.

Appearance	Red, Smooth and Tacky	
Worked Penetration	270 mm	ASTM D217
Oil Viscosity	1900 cSt@40°C Typical	
Timken OK Load	30	ASTM D2509
4 Ball Weld Test	480 kg	ASTM D2596

## APPLICATION

Prosuperplant Grease is the ideal recommendation for use in extreme heavy-duty applications and where high thermal resistance is a must. These applications include all industrial, earthmoving, agricultural, automotive and marine equipment.

Prosuperplant Grease is also suitable for high shock load applications such as excavator and loader bucket pins.

The recommended temperature range is from -20 °C to 185 °C, however Prosuperplant Grease may be used at temperatures to 200°C with the lubrication frequency increased accordingly.

## STANDARDS

NLGI Grade No.2

## CONTAINER SIZES

Bulk Bin, 180 kg, 55 kg, 20 kg, 2.5 kg, 450g Cartridges

Issue Date 1/9/2019

*Proven Protection. Powerful Performance.*