



PRODUCT DATA SHEET

BREAKOUT BLUE

LUBRICATION BEYOND OIL AND GREASE

DESCRIPTION

TALCOR BREAKOUT BLUE is an antiseize with a very distinctive blue colour because of its revolutionary formulation, consisting of the new generation of bio-stable anti-weld fillers, highly refined, high viscosity base stocks, all thickened with a high melt complex soap.

TYPICAL APPLICATION

All drill rod, tubes and flanges that are constantly connected and disconnected.

BENEFITS

- Contains **no heavy metal fillers** or additives.
- Adhesive and cohesive properties ensure excellent adhesion, even in wet conditions, whilst minimising fling-off.
- High drop point complex thickener provides excellent pumpability and good stability at high temperatures.
- Will not build up in thread roots, yet leaves sufficient coverage to extend relubrication cycles.

NOTES

Due to anti-weld characteristics of **Breakout Blue** it is not recommended for general purpose greasing.



PRODUCT DATA SHEET

BREAKOUT BLUE

LUBRICATION BEYOND OIL AND GREASE

TYPICAL PROPERTIES

NLGI Grade	1
Thickener	Complex Based
Dropping Point °C	266
Base Fluid Viscosity cSt @ 40°C	400
Safe Operating Temperature °C	152
Four Ball EP Test Weld Point (kgf)	500
TSP Additive System	Severe Duty

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. It is the user's obligation to evaluate and use the product safely and to comply with all applicable laws and regulations.

Specifications as at September 2003