

PRODUCT DATA SHEET

MULTITEC 10W40 SN CF

(SEMI-SYNTHETIC PREMIUM ENGINE OIL)

DESCRIPTION

Multitec 10W40 SN CF is a latest generation semi-synthetic, multi-application engine oil using the latest additive technology to provide excellent performance in late model petrol and diesel engines. It provides the performance reserve required for oil in modern technology, fine tolerance, high stress applications. It provides the maximum protection against wear, corrosion, oxidisation and sludge formation and it gives superior protection where vehicles encounter lower temperature operation with cold starts.

Viscosity - Typical 13.1 cSt @ 100°C

APPLICATION

This oil is designed for most modern petrol and diesel engines, both naturally aspirated and turbocharged. It is particularly suitable for multi-valve multi-cam models requiring lower viscosity oil for fuel economy, low emissions and high performance.

It is also well suited to four stroke motor cycles with wet clutches. This product may not be suitable for modern diesel engines fitted with diesel particulate filters (DPFs).

STANDARDS

Meets or exceeds the following:

SAE Grade: 10W40

API: SL SN CF

ACEA: A3/B3-16 A3/B4-16 A5/B5-16

MB 229.1 229.3

VW 501 01, 502 00, 505 00

Renault RN0700, 0710

PSA B71 2300

Ford WSS-M2C913-D

Jaguar Land Rover ST JLR.03.5003

JASO MA

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres, 1 Litres

Issue Date 1/09/2019

Proven Protection. Powerful Performance.