



PRODUCT INFORMATION SHEET

**Product Name: COMPTec ASHLESS ISO 46, 68
COMPRESSOR OIL**

PRODUCT

Prolube Comptec Ashless Compressor Oil is blended from semi synthetic and highly refined virgin base oils, with anticorrosion, anti-oxidisation and ashless anti-wear additives. The product also has good anti-foam and excellent thermal resistance properties.

Product	46	68
Viscosity	46	68
Typical cSt @ 40°C		

APPLICATION

Suitable for use in all types of reciprocating air compressors and high performance drip feed rotary or screw compressors and vacuum pumps. The superior base oils and ashless additive package provide for reduced carbon and ash deposits in valves and discharge lines. A long service life can be expected over a wide range of operating temperatures.

Viscosity choice should be according to manufacturer's recommendations.

STANDARDS

- DIN 51506 (VBL, VCL, VDL)
- ISO / DP 6521 (DAA, DAB, DAH, DAG)
- DIN 51524 Part 1
- Siemens TLV 9013
- British Standard BS 489
- US Steel 120

CONTAINER SIZES

205 Litres,

20 Litres,

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au

Issue Date 26/6/2012