

PRODUCT DATA SHEET

HYPLEX ZF SERIES ISO 22 32 46 68 100

(ZINC FREE HYDRAULIC OILS)

DESCRIPTION

Zinc Free Hydraulic Oils are blended from high quality virgin base stocks and special additives that allow their use in hydraulic systems, which have equipment with silver bearing surfaces. These oils contain anti-corrosion, anti-oxidant and antiwear additives and provide high resistance to thickening in service. They are totally zinc-free.

Grade	22	32	46	68	100
Viscosity (Typical cSt @ 40°C)	22	32	46	68	100
Viscosity (Typical cSt @ 100°C)	4.7	6.0	7.8	10.1	13.5

APPLICATION

Use in all hydraulic systems and, in particular, in hydraulic systems with components with silver bearing surfaces that are vulnerable to attack from standard hydraulic oils.

STANDARDS

Meets or Exceeds the following:

DIN 51524, Part 1 (HL), Part 2 (HLP), Part 3 (HVLP)

Denison HF-1, HF-2, HF-0

Cincinnati Machine P68, P69, P70

ISO 6743/4 HM, HV

US Steel 120 136, 127

AFNOR NF-E 48-603 HM, HV

Swedish Standard SS 155434

VDMA 24318

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres

Issue Date 1/9/2019

Proven Protection. Powerful Performance.