

## PRODUCT DATA SHEET

# AGLUBE HTX (HARVESTER HYDRAULIC OIL)



## DESCRIPTION

Aglube HTX is an exceptionally shear stable hydraulic oil with excellent anti-wear, anti-foam, anti-corrosion and antioxidant properties. It has a very high viscosity index which prevents thinning out at high temperature.

Viscosity - ISO 68 - Typical 68 cSt@40°C

Viscosity Index - Typical 149

## APPLICATION

Specifically blended to meet the stringent requirements of AUSTOFT and CAMECO DOWN UNDER cane harvesters but can be used in all hydraulic applications where high temperature and severe working conditions exist.

## STANDARDS

Meets performance requirements of all major hydraulic pump manufacturers including

Vickers	1-286-S, M-2950-S
DIN 51524	Part 1, 2, 3
Parker Hannifin	HF-0
Lee Norse	100-1
US Steel	136, 127
Eaton Brochure	03-401-2010
General Motors	LH-04-1, LH-06-1, LH-15-1
AFNORE	48-603
ISO	11158
Cincinnati Milacron	P-68, P-69, P-70

Racine variable volume vane pumps.

It is NOT for use in hydraulic equipment with silver bearing surfaces.

## CONTAINER SIZES

205 Litres, 20 Litres

Issue Date 1/9/2019