

PRODUCT DATA SHEET

AGLUBE HTX (HARVESTER HYDRAULIC OIL)



DESCRIPTION

Aglube HTX is an exceptionally shear stable hydraulic oil with excellent anti-wear, anti-foam, anti-corrosion and antioxidant properties. It has a very high viscosity index which prevents thinning out at high temperature.

Viscosity - ISO 68 - Typical 68 cSt@40°C

Viscosity Index - Typical 149

APPLICATION

Specifically blended to meet the stringent requirements of AUSTOFT and CAMECO DOWN UNDER cane harvesters but can be used in all hydraulic applications where high temperature and severe working conditions exist.

STANDARDS

Meets performance requirements of all major hydraulic pump manufacturers including

| | |
|---------------------|---------------------------|
| Vickers | 1-286-S, M-2950-S |
| DIN 51524 | Part 1, 2, 3 |
| Parker Hannifin | HF-0 |
| Lee Norse | 100-1 |
| US Steel | 136, 127 |
| Eaton Brochure | 03-401-2010 |
| General Motors | LH-04-1, LH-06-1, LH-15-1 |
| AFNORE | 48-603 |
| ISO | 11158 |
| Cincinnati Milacron | P-68, P-69, P-70 |

Racine variable volume vane pumps.

It is NOT for use in hydraulic equipment with silver bearing surfaces.

CONTAINER SIZES

205 Litres, 20 Litres

Issue Date 1/9/2019

Proven Protection. Powerful Performance.