



PRODUCT INFORMATION SHEET

Product Name: White Oil 15

PRODUCT

Prolube White Oil 15 is a white mineral oil specially processed and packaged to ensure full compliance with purity standards for use as a processing aid to lubrication oil in food, pharmaceutical and agricultural industries.

Special Handling Note: While the inclusion of an FDA approved inhibitor in Prolube White Oil 68 greatly extends shelf life all white oils may darken and develop an odour if exposed to direct sunlight or stored at high temperatures. Accordingly White Oil should be stored at room temperatures or lower.

Viscosity ISO 15 Typical 15 cSt @ 40°C

APPLICATION

Prolube White Oil 15 is recommended for a variety of applications in the pharmaceutical and food industries and for general industrial applications where pharmaceutical grade white oil is required.

Typical applications include the following.

- Pharmaceutical and cosmetic preparations such as ointments, and as carriers in the preparation of many curative drugs.
- Food processing and packaging operations where lubricating oil used as a processing aid may be included in food or food packaging material, or where direct contact between the lubricating, hydraulic, or rust proofing oil and food packaging material may occur.
- As an hydraulic fluid or bearing and gear lubricant in food processing and packaging machinery.
- General Industry, including: as a plasticiser for hydrocarbon resins; as process oil where extremely low sulphur contents are required; as a lubricant for sewing, knitting and cloth cutting machines where stainless oil is required; agricultural sprays; organic synthesis; plastics manufacture and animal husbandry.

STANDARDS

- British Pharmacopoeia (BP)
- US National Formulary
- US Food & Drug Administration (FDA) Regulations CFR 172.878, 178.3620(a), 178.3570 and 573.680.
- US Pharmacopoeia (USP)
- Deutches Arzneibuch (DAB)

(Department of Primary Industries and Energy, Australian Quarantine and Inspection Service (AQIS) Type A Lubricants)

CONTAINER SIZES

205 Litres (Food grade)

20 Litres. (Industrial grade only)

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au

Issue Date 26/6/2012