

PRODUCT DATA SHEET

SYNTEGRA PRO 60 10W60

(ULTRA PERFORMANCE SYNTHETIC ENGINE OIL)

DESCRIPTION

Syntegra PRO 60 is an ultra-high performance synthetic engine oil which combines extreme performance additive technology and polyalphaolefin (PAO) base stock to provide lubricating oil with the highest level of protection to ensure maximum engine longevity. Syntegra PRO 60 provides superior high temperature stability, easy cold cranking, reduced oil consumption and improved engine cleanliness.

	ASTM METHOD	TYPICAL RESULTS
Specific Gravity	D1298	0.850
Viscosity (Typical cSt @ 100°C)	D445	22.5 cSt
Viscosity (Typical cSt @ 40°C)	D445	145 cSt
Viscosity CCS @ -25 °C	D5293	6190 cP
Viscosity HTHS	D4683	5.76 cP
Viscosity Index	D2270	177
Pour Point	D97	-35 °C
Flash Point COC	D92	235 °C
Total Base Number	D2896	8.85 mg KOH/g
Sulphated Ash	D874	1.065 % wt
Zinc	D4951	0.115 % wt
Appearance	Visual	Florescent

APPLICATION

Syntegra PRO 60 is designed for high performance four stroke petrol engines of cars, motor cycles and light duty diesel engines that require a high viscosity oil. Syntegra Pro 60 is ideally suitable for turbocharged, super charged or naturally aspirated large bore race and street engines that are subjected to high stress conditions.

STANDARDS

Meets or Exceeds the following:

SAE Grade: 10W60

API: SN/CF

ACEA: A3/B4 – 2016

MB 229.1, VW 502 00/505 00

CONTAINER SIZES

205 Litres, 5 Litres

Issue Date 1/9/2020