

**PRODUCT DATA SHEET****HVX MS**  
**(15W50 SL CF)****DESCRIPTION**

HVX MS engine oil has modern technology for late model, high stress applications. It provides the maximum protection against wear, corrosion, oxidation and sludge formation and is particularly suitable for naturally aspirated and turbo-charged models. HVX MS oil can be used in light and medium duty diesel engines and it provides enhanced valve train lubrication in modern unleaded petrol and LP gas motors. This product is also suitable for four stroke motorcycles fitted with wet clutches.

Viscosity - Typical 18.3 cSt @ 100°C

**APPLICATION**

This oil is designed for all 4 stroke and rotary petrol motors using ULP, PULP and LP gas fuels and requiring an SAE 15W50 engine oil. Although it was specifically designed for post-1997 model motors, including multi-valve and turbo-charged motors, it is also suitable for light duty passenger car style diesel motors.

**STANDARDS**

Meets or exceeds the following:

SAE Grade: 15W50

API: SL CF

ACEA: A3/B3-04

MB 229.1

VW 505 00

JASO MA

**CONTAINER SIZES**

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres

Issue Date 1/9/2019

*Proven Protection. Powerful Performance.*