

PRODUCT DATA SHEET

HVX MULTI-V 10W30

A blurred, high-angle photograph of a car, showing the front and side profile, with a focus on the wheels and the front end. The image is semi-transparent and serves as a background for the product title.

DESCRIPTION

HVX Multi-V 10W30 engine oil uses the latest additive technology to provide excellent performance in late model petrol engines. It is suitable for naturally aspirated and turbocharged motors. The formulation is designed to give excellent low temperature protection while also having low friction characteristics to optimise fuel consumption. This product is engineered to prevent the harmful build-up of sludge, reduce oil deposits and provide daily protection for your engine providing superior component protection at cold start-up.

Viscosity - Typical 10.7 cSt @ 100°C

APPLICATION

This oil is designed for late model 4-stroke petrol motors, particularly multi-valve, multi-cam models requiring lower viscosity oils for fuel economy, low emissions and high performance. It has been formulated for applications where 5W30 to 10W30 engine oils are specified.

STANDARDS

Meets or exceeds the following:

SAE Grade: 10W30

API: SN CF

ILSAC: GF-5

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres, 1 Litres

Issue Date 1/9/2019

Proven Protection. Powerful Performance.