

PRODUCT DATA SHEET

HVX MULTI-V 10W30

(SEMI-SYNTHETIC PREMIUM ENGINE OIL)

DESCRIPTION

HVX Multi-V 10W30 engine oil utilises semi synthetic base oils and the latest additive technology to provide excellent performance in late model petrol engines. It is suitable for naturally aspirated and turbocharged motors. The formulation is designed to give excellent low temperature protection while also having low friction characteristics to optimise fuel consumption. This product is engineered to prevent the harmful build-up of sludge, reduce oil deposits, protect against Low Speed Pre-ignition (LSPI) and provide daily protection for your engine providing superior component protection at cold start-up.

Viscosity - Typical 10.7 cSt @ 100°C

APPLICATION

This oil is designed for late model 4-stroke petrol motors, particularly multi-valve, multi-cam models requiring lower viscosity oils for fuel economy, low emissions and high performance. It has been formulated for applications where 5W30 to 10W30 engine oils are specified. HVX Multi V 10W30 is suitable for use where Dexos 1 is specified.

STANDARDS

Meets or exceeds the following:

SAE Grade: 10W30

API: SN, SN Plus, SP, CF

ILSAC: GF-5, GF-6A

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres, 1 Litres

Issue Date 16/8/22