



PRODUCT INFORMATION SHEET

Product Name: EUROFLEET 15W40 CI-4

PRODUCT

Prolube Eurofleet CI-4 SHPD is a Super High Performance Diesel multigrade engine oil which gives outstanding performance in European turbo-charged diesel engines. It is especially effective in reducing oil consumption and resists bore polishing. It is recommended particularly where extended oil drains are anticipated.

Viscosity (Typical)	15.0 cSt @ 100°C 124 cSt @ 40°C
Viscosity Index	123
TBN	10.12 mg KOH/g
Sulphated Ash	1.42 mass/wt-%

APPLICATION

The primary recommendation is for long haul, European style diesels. Eurofleet is suitable for electronically controlled engines, where high soot loading is experienced and for extended drain or severe service conditions. Extended drain intervals should be in compliance with the engine manufacturer guidelines and in conjunction with oil analysis checks.

STANDARDS

Meets or exceeds the following or is recommended for:

SAE Grade: 15W40	
ACEA: A3/B3/B4-10 E7-08 E7/B4/A3-07 E7/B4/B3/A3-04 E5/E3/B4/B3/A3-02	
API CI-4, CH-4/SL, SJ	
Mercedes MB 228.2 228.3	Volvo VDS 3
Renault RLD2	MAN 3275
MTU Type 2	CAT ECF 1a, ECF-2
CUMMINS CES 20076, 77, 78	Mack EO-M PLUS

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: [admin@prolube .com.au](mailto:admin@prolube.com.au)
Internet: www.prolube.com.au

Issue Date 16/1/2014