

## PRODUCT DATA SHEET

# HYPLEX SPINDLE OIL SERIES

## DESCRIPTION

Hyplex Spindle Oils are blended from HVI virgin base stocks and contain a special thermally stable ashless additive which inhibits oxidation, protects bearings from corrosion and prevents wear. Hyplex Spindle Oil is specially formulated to provide excellent protection against Rust and Oxidation.

<b>Grade</b>	<b>6</b>	<b>10</b>
Viscosity (Typical cSt @ 40°C)	7.7	9.5
Viscosity (Typical cSt @ 100°C)	2.4	2.8
Viscosity Index	125	125
Density @ 15 °C kg/litre	0.850	0.822
Flash Point °C	146	>140
Pour Point °C	-63	-30

## APPLICATION

Hyplex Spindle Oil provides excellent performance in high speed bearings, machine tool spindles and some high performance hydraulics.

## STANDARDS

Meets or Exceeds the following:

DIN 51524, Part 2 (HLP) and Part 3 (HVLP)

Denison HF-1, HF-2, HF-0

AFNOR E48-603 HL

Cincinatti Machine P38, P55, P54, P57 P62

## CONTAINER SIZES

205 Litres, 20 Litres

Issue Date 1/9/2019

*Proven Protection. Powerful Performance.*