

PRODUCT DATA SHEET

AGTRANS HFD Series

(FINAL DRIVE OIL)



DESCRIPTION

Agtrans HFD 50 and Agtrans HFD 60 are premium heavy duty final drive lubricants which are specifically developed to meet the Caterpillar FD-1 Specification. These lubricants contain a high level of anti wear additive to provide superior protection for heavily loaded final drives and axles. These lubricants also allow extended drain intervals to 4000 hours with regular oil analysis.

	50	60
Viscosity (cSt @ 40°C Typ)	225	330
Viscosity (cSt @ 100°C)	19.6	25.2
SAE Viscosity	50	60

APPLICATION

Agtrans HFD oils are the primary recommendation for final drives and axles in off highway trucks, large track type tractors, loaders, skidders and pipe layers. Though specifically designed to meet the Caterpillar specification, these oils are also suitable for Komatsu and other heavy duty offroad equipment. Agtrans HFD lubricants are used where products meeting Cat Specification TO-4 do not provide sufficient protection.

Important: Agtrans HFD oils must NOT be used in compartments containing friction materials or wet brakes.

STANDARDS

Meets performance requirements of major off-road transmission manufacturer including:

Caterpillar	Specification FD-1
Komatsu	

CONTAINER SIZES

1000 Litres IBC, 205 Litres, 20 Litres

Issue Date 1/9/2019