



Lidomont Pty Ltd Trading as **Prolube Lubricants**  
15 Pinnacle Street Brendale QLD 4500 | Ph: 07 3881 1733  
[sales@prolube.com.au](mailto:sales@prolube.com.au) | [www.prolube.com.au](http://www.prolube.com.au)  
ABN: 64 010 867 428

## PRODUCT DATA SHEET

# MONOTEC 30

(SAE 30 CD SF)

## DESCRIPTION

Monotec 30 is a SAE 30 oil originally developed to meet the Caterpillar Series 3 and Allison C3 requirements. It is recommended also for use in GM Detroit diesel engines, which require oil with a low sulphated ash residue. It can be used in petrol and diesel engines where monograde oil is preferred. It can be used also as hydraulic oil for earthmoving machinery.

Viscosity - Typical 11.5 cSt @ 100°C

## APPLICATION

Designed for engines, transmissions and hydraulic systems where SAE 30 monograde oil is specified or indicated. It is particularly suitable for older style diesel motors that may react unfavourably to modern, multigrade engine oils. Its primary recommendation is as a running-in oil for rebuilt and reconditioned petrol and diesel motors subject to manufacturer's specification.

## STANDARDS

Meets or exceeds the following:

SAE Grade: 30  
API: CD SF

## CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres

Issue Date 1/9/2019

*Proven Protection. Powerful Performance.*