

PRODUCT DATA SHEET

ULTRAFLEET 15W40 CI-4 SL

(HIGH PERFORMANCE DIESEL ENGINE OIL)

DESCRIPTION

Ultrafleet 15W40 has been formulated using new generation high performance base oils and the most recent additive technology to meet the latest CI-4 performance requirements. Ultrafleet 15W40 provides optimum protection and control of corrosion, oil thickening due to soot build up, piston deposits, oxidation, sludge build up and high temperature stability.

APPLICATION

Ultrafleet is a high performance mixed fleet lubricant designed for use in the latest European, US and Japanese four stroke diesel engines, including the new breed highly turbocharged and emission control designed engines. Ultrafleet is our primary recommendation for electronically controlled engines, where high soot loading is experienced and for extended drain or severe service conditions. Extended drain intervals should be in compliance with the engine manufacturer guidelines and in conjunction with oil analysis checks.

STANDARDS

Meets or exceeds the following:

SAE Grade: 15W40

API: CI-4, CH-4, SL, SJ

CUMMINS CES 20076, 77, 78

MACK EO-M PLUS, EO-N

ACEA: E7-16 A3/B4-16

Detroit DDC 93K215

Mercedes MB 228.2 228.3

Volvo VDS 3

Renault RLD2

MAN 3275

MTU Type 2

CAT ECF 1a, ECF-2

Deutz DQC III-10

Global DHD-1

Allison TES439

CONTAINER SIZES

Bulk, 1000 Litre IBC, 205 Litres, 60 Litres, 20 Litres, 10 Litres, 5 Litres, 1 Litre

Issue Date 1/9/2019

Proven Protection. Powerful Performance.