



Lidomont Pty Ltd Trading as **Prolube Lubricants**
15 Pinnacle Street Brendale QLD 4500 | Ph: 07 3881 1733
sales@prolube.com.au | www.prolube.com.au
ABN: 64 010 867 428

PRODUCT DATA SHEET

PREMIUM 15W40 SN CF **(FOUR STROKE PREMIUM ENGINE OIL)**

DESCRIPTION

Premium 15W40 SN CF four stroke engine oil uses the latest additive technology to provide excellent performance in late model petrol and light duty diesel engines. It is suitable for naturally aspirated and turbocharged motors. The formulation is designed to give excellent protection for the modern multi cam engines and is engineered to prevent the harmful build-up of sludge, reduce oil deposits and provide daily protection for your engine and superior component protection at cold start-up.

Viscosity - Typical 15.0 cSt @ 100°C

APPLICATION

This oil is designed for economy workshop servicing of late model 4-stroke petrol and diesel engines, particularly multi-valve, multi-cam models where medium viscosity oils provide improved high temperature high stress performance.

STANDARDS

Meets or exceeds the following:

SAE Grade: 15W40

API: SN CF

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres,

Issue Date 1/9/2019

Proven Protection. Powerful Performance.