



PRODUCT DATA SHEET

TRUCK N FARM GREASE

DESCRIPTION

Prolube Truck N Farm Grease comprises a lithium complex base thickener with selected synthetic and paraffinic base oils combined with rust, oxidation and corrosion inhibitors, tackiness adhesives and additional more effective extreme pressure additives to cater for unusually high load service conditions.

It protects against wear on all moving parts and shock loading in unusually high load services. It prevents scuffing and further assists in wear prevention because Truck N Farm Grease has excellent shear stability as well as the high load extreme pressure characteristics.

Appearance	Red, Smooth and Tacky	
Worked Penetration	270 mm	ASTM D217
Oil Viscosity	1200 cSt@40°C	Typical
Timken OK Load	28 kg	ASTM D2509
4 Ball Weld Test	> 500 kg	ASTM D2596

APPLICATION

Prolube Truck N Farm Grease is the ideal grease for slow speed, high load, high shock applications and where water wash out or mud and grit ingress is an issue. Applications include earthmoving, quarry and mining, marine, agriculture, dredging, logging and forestry industries. Excellent in pin and bush applications, slow speed bearings, gears, couplings, turntables, shackles and many other general purpose applications.

Prolube Truck N Farm Grease is not suitable for high speed bearings such as electric motors and highway automotive wheel bearings. In these applications use Prolithtac or Syntac HT2.

STANDARDS

NLGI Grade No.2

CONTAINER SIZES

450g Cartridges

Issue Date 28/5/2020

Proven Protection. Powerful Performance.