

PRODUCT DATA SHEET

SYNTEGRA PRO 40 10W40

(ULTRA-HIGH PERFORMANCE FULL SYNTHETIC ENGINE OIL)

DESCRIPTION

Syntegra PRO 40 is an ultra-high performance full synthetic engine oil which combines the latest development in additive technology and polyalphaolefin (PAO) base stock to provide a lubricating oil with the highest level of protection to ensure maximum engine longevity. Syntegra PRO 40 provides extra wear protection with zinc boost to give superior protection in extreme conditions. It is also formulated to provide high temperature stability, easy cold cranking, reduced oil consumption and improved engine cleanliness.

	ASTM METHOD	TYPICAL RESULTS
Specific Gravity	D1298	0.850
Viscosity (Typical cSt @ 100°C)	D445	14.0 cSt
Viscosity (Typical cSt @ 40°C)	D445	97.7 cSt
Viscosity CCS @ -25 °C	D5293	6900 cP
Viscosity HTHS	D4683	4.2 cP
Viscosity Index	D2270	146
Pour Point	D97	-35 °C
Flash Point COC	D92	235 °C
Sulphated Ash	D874	1.5 % wt
Zinc	D4951	0.22 % wt

APPLICATION

Syntegra PRO 40 is designed for high performance 4, 6, V6 and V8 four stroke gasoline engines of cars, as well as high performance light vehicle diesel engines operating under extreme race conditions. Syntegra Pro 40 is ideally suitable for turbocharged, super charged or naturally aspirated race and street engines that are subjected to high stress conditions.

STANDARDS

Meets or Exceeds the following:

SAE Grade: 10W40

ACEA: A3/B3 - 2016

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres

Issue Date 31/3/2020