

PRODUCT DATA SHEET

SYNTEGRA MT 75W-80

(FULL SYNTHETIC GL-4 GEAR OIL)

DESCRIPTION

Syntegra MT 75W-80 gear oil is a premium full synthetic GL-4 manual transmission lubricant designed for modern vehicles specifying low viscosity product to achieve improved fuel economy and long life.

Syntegra MT 75W-80 improves gear shift performance where higher viscosity products, may be causing difficulty. It has been designed to overcome metal fatigue, wear and seizure normally associated with low viscosity, by maintaining the oil film thickness and improving the wear characteristics with additives.

Being a low viscosity product, it also gives extended drain intervals, and excellent thermal stability. Syntegra MT 75W-80 is also compatible with mineral oils so there is no need for a major flush to be carried out prior to changeover under normal circumstances.

Viscosity: Typical 9.3 cSt @ 100°C

APPLICATION

Syntegra MT 75W-80 is recommended for synchronized or non-synchronized manual gearboxes, transaxles and transfer cases where the manufacturer specifies API GL-4 75W-80 viscosity oil. This product is recommended for DAF, Iveco, MAN, and Renault trucks with ZF transmissions, MB, Voith and Volvo manual and automated manual transmissions with or without interarder. Extended drain intervals should be regularly monitored through laboratory analysis.

STANDARDS

Meets or exceeds the following:

SAE Grade: 75W-80

API: GL-4

Suitable for use where the following manufacturers' specifications are indicated:

ZF TE-ML 01L / 02L / 16K

Eaton 300000 km 3 Years

MAN 341 Type Z4

VOLVO 97307

MB 235.29

VOITH CLASS C

CONTAINER SIZES

205 Litres, 20 Litres

Issue Date: 1/2/23