

PRODUCT DATA SHEET

TRANSAX LS90 & LS85W140 GL5

DESCRIPTION

Transax LS90 and LS85W140 are special products that are used in certain types of limited slip differentials. As well as meeting all normal requirements for SAE 90 and 85W140 gear oils, they have a special supplement that enhances their performance as a rear axle lubricant. The premium additive pack provides excellent anti-wear, anti-corrosion, anti-oxidisation and extreme pressure protection and allows use in normal gear applications and enhanced performance in limited slip differentials.

Grade	LS90	LS85W140
Viscosity (Typical cSt @ 40°C)	148	350
Viscosity (Typical cSt @ 100°C)	15	25.5

APPLICATION

These gear oils are designed for passenger vehicles, light trucks, heavy trucks and off-road equipment fitted with limited slip differentials.

STANDARDS

Meets or exceeds the following requirements:

SAE Grade: LS90, LS85W140

API: GL5 (GL6 Obsolete) MT-1

MACK: GO-J

MIL-PRF-2105D MIL-PRFP2105E

ZF TE – ML 05C, 12C, 16E, 21C

Arvin Meritor Axles

BTR Limited Slip (LS90: BTR 5M-50 LS85W140: BTR 5M-48)

GM Limited Slip (LS90: HN 2013 LS85W140: HN 2040)

Dana

SAE J2360

CONTAINER SIZES

Bulk, 1000 Litre IBC, 205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre

Issue Date 21/5/2020