



PRODUCT INFORMATION SHEET

Product Name: TRANSAX LS90 and LS85W140 GL5

PRODUCT

Prolube Transax LS90 and LS85W140 are special products that are used in certain types of limited slip differentials. As well as meeting all normal requirements for SAE 90 and 85W140 gear oils, they have a special supplement that enhances their performance as a rear axle lubricant. The premium additive pack provides excellent anti-wear, anti-corrosion, anti-oxidisation and extreme pressure protection and allows use in normal gear applications and enhanced performance in limited slip differentials.

Grade	LS90	LS85W140
Viscosity (Typical cSt @ 40°C)	148	350
Viscosity (Typical cSt @ 100°C)	15	25.5

APPLICATION

These gear oils are designed for passenger vehicles, light trucks, heavy trucks and off-road equipment fitted with limited slip differentials.

STANDARDS

Meets or exceeds the following specifications or is suitable for use :
SAE Grade: 80W90, SAE 90 - SAE 140, 85W140.
API: GL5
MACK: GO-J
MIL-L-2105D MIL-PRF-2105E.
ZF TE – ML 05C, 12C, 16E, 21C
Arvin Meritor Axles

CONTAINER SIZES

205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinnacle Street,
Brendale, Qld. 4500.

Telephone: (07) 3881 1733
Fax: (07) 3881 1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au

Issue Date 27/9/2012